

MICROFARAD TABLE						
KVAR	480V / 3Φ / 60Hz		600V / 3Φ / 60Hz		240V / 3Φ / 60Hz	
	min uF	max uF	min uF	max uF	min uF	max uF
1	5.8	6.6	3.7	4.2	23.0	26.5
1.5	8.6	9.9	5.5	6.4	34.5	39.7
2	11.5	13.2	7.4	8.5	46.1	53.0
2.5	14.4	16.5	9.2	10.6	57.6	66.2
3	17.3	19.9	11.1	12.7	69.1	79.4
4	23.0	26.5	14.7	16.9	92.1	105.9
5	28.8	33.1	18.4	21.2	115.1	132.4
6	34.5	39.7	22.1	25.4	138.2	158.9
7	40.3	46.3	25.8	29.7	161.2	185.4
7.5	43.2	49.6	27.6	31.8	172.7	198.6
8	46.1	53.0	29.5	33.9	184.2	211.8
9	51.8	59.6	33.2	38.1	207.2	238.3
10	57.6	66.2	36.8	42.4	230.3	264.8
11	63.3	72.8	40.5	46.6	253.3	291.3
12	69.1	79.4	44.2	50.8	276.3	317.8
12.5	72.0	82.7	46.1	53.0	287.8	331.0
13	74.8	86.1	47.9	55.1	299.3	344.2
14	80.6	92.7	51.6	59.3	322.4	370.7
15	86.3	99.3	55.3	63.6	345.4	397.2
16.66	95.9	110.3	61.4	70.6	383.6	441.2
17.5	100.7	115.8	64.5	74.1	403.0	463.4
18	103.6	119.2	66.3	76.3	414.5	476.6
20	115.1	132.4	73.7	84.7	460.5	529.6
21	120.9	139.0	77.4	89.0	483.5	556.1
22.5	129.5	148.9	82.9	95.3	518.1	595.8
25	143.9	165.5	92.1	105.9	575.6	662.0
27.5	158.3	182.0	101.3	116.5	633.2	728.2
30	172.7	198.6	110.5	127.1	690.8	794.4
32.5	187.1	215.1	119.7	137.7	748.3	860.6
35	201.5	231.7	128.9	148.3	805.9	926.8
37.5	215.9	248.2	138.2	158.9	863.5	993.0
40	230.3	264.8	147.4	169.5	921.0	1059.2
42.5	244.7	281.3	156.6	180.1	978.6	1125.4
45	259.0	297.9	165.8	190.7	1036.2	1191.6
47.5	273.4	314.4	175.0	201.2	1093.7	1257.8
50	287.8	331.0	184.2	211.8	1151.3	1324.0
52.5	302.2	347.5	193.4	222.4	1208.9	1390.2
55	316.6	364.1	202.6	233.0	1266.4	1456.4
60	345.4	397.2	221.0	254.2	1381.6	1588.8
65	374.2	430.3	239.5	275.4	1496.7	1721.2
70	403.0	463.4	257.9	296.6	1611.8	1853.6
75	431.7	496.5	276.3	317.8	1726.9	1986.0
80	460.5	529.6	294.7	338.9	1842.1	2118.4
85	489.3	562.7	313.2	360.1	1957.2	2250.8
90	518.1	595.8	331.6	381.3	2072.3	2383.2
100	575.6	662.0	368.4	423.7	2302.6	2648.0